

Arcair® Professional Air Carbon-Arc Electrodes

Features & Benefits

Designed specifically for the air carbon-arc process

- ★ Contain a precise formulated blend of carbon and graphite
- ★ Produces the most efficient metal removal performance in today's market
- ★ Superior metal removal rates, cool operation, and uniform diameters

Ideal for a broad range of applications

- ★ Creating U-grooves for weld joint
- ★ Removing old welds
- ★ Gouging out cracks
- ★ Cleaning and repairing castings
- ★ Removing hard surface material
- ★ Rough machining



POINTED COPPLERCLAD DC ELECTRODES

Part No.	Description	Application
22-023-003 *	1/8" (3.2 mm) x 12" (30.5 cm)	A standard, all purpose gouging electrode. Its controlled copper coating improves electrical conductivity (for more efficient, cooler operation) and helps maintain electrode diameter at the point of the arc.
22-983-003	5/32" (4.0 mm) x 12" (30.5 cm)	
22-033-003	3/16" (4.8 mm) x 12" (30.5 cm)	
22-043-003	1/4" (6.4 mm) x 12" (30.5 cm)	
22-053-003	5/16" (7.9 mm) x 12" (30.5 cm)	
22-063-003	3/8" (9.5 mm) x 12" (30.5 cm)	
22-082-003	1/2" (12.7 mm) x 14" (35.6 cm)	

Note: Standard 50 pieces per carton unless noted

* 100 pieces per carton




POINTED PLAIN DC ELECTRODES

Part No.	Description	Application
21-983-003	5/32" (4.0 mm) x 12" (30.5 cm)	General purpose electrodes without the copper plating to avoid any chance of copper contamination in the base material. Same high quality blend of carbon and graphite used in other electrodes.
21-033-003	3/16" (4.8 mm) x 12" (30.5 cm)	
21-043-003	1/4" (6.4 mm) x 12" (30.5 cm)	
21-053-003	5/16" (7.9 mm) x 12" (30.5 cm)	
21-063-003	3/8" (9.5 mm) x 12" (30.5 cm)	
21-083-003	1/2" (12.7 mm) x 14" (35.6 cm)	

Note: Electrodes will glow incandescent due to not having the copper plating and a penciling affect will take place along the outside diameter of the electrode. Standard 50 pieces per carton unless noted

Arcair®



FLAT COPPERCLAD DC ELECTRODES

Part No.	Description	Application
35-099-003	5/8" (15.9 mm) x 3/16" (4.8 mm) x 12" (30.5 cm)	Specially designed for close tolerance metal removal and scarfing applications. Excellent for general gouging applications, removing weld crowns, repairing or making dies, removing temporary welded dogs, and scarfing billets.
35-033-003	3/8" (9.5 mm) x 5/32" (4.0 mm) x 12" (30.5 cm)	

Note: Standard 50 pieces per carton unless noted



HALF ROUND COPPERCLAD DC

Part No.	Description	Application
25-103-003	5/8" (15.9 mm) x 12" (30.5 cm)	Versatility of having both a round and flat electrode for the various gouging applications. Excellent for removing weld crowns, repairing or making dies, removing temporary welded dogs, and scarfing billets.

Note: Standard 50 pieces per carton unless noted

JOINTED JETRODS[®] COPPERCLAD DC

Part No.	Description	Application
24-052-003	5/16" (7.9 mm) x 14" (35.6 cm)	Provides continuous electrode feed and increased savings, especially in production operations. Suited for both hand held foundry applications and or automated gouging systems.
24-062-003	3/8" (9.5 mm) x 14" (35.6 cm)	
24-064-003	3/8" (9.5 mm) x 17" (43.2 cm)	
24-082-003	1/2" (12.7 mm) x 14" (35.6 cm)	
24-084-003	1/2" (12.7 mm) x 17" (43.2 cm)	
24-104-003	5/8" (15.9 mm) x 17" (43.2 cm)	
24-124-003	3/4" (19.5 mm) x 17" (43.2 cm)	

Note: Standard 100 pieces per carton unless noted

POINTED COPPERCLAD AC ELECTRODES

Part No.	Description	Application
20-033-003	3/16" (4.8 mm) x 12" (30.5 cm)	Designed for use with A.C. power supplies. Rare earth material is added to the electrodes to stabilize the arc and enhance the operating characteristics.
20-043-003	1/4" (6.4 mm) x 12" (30.5 cm)	
20-063-003	3/8" (9.5 mm) x 12" (30.5 cm)	