

3M Industrial Adhesives & Tapes Division
3M™ Performance Yellow Masking Tape 301+

101+

201+

301+

401+

501+



3

The
dependable
choice for industrial
performance

301+



3M


3M™ Performance Yellow Masking Tape 301+



When it comes to industrial paint masking, 3M™ Performance Yellow Masking Tape 301+ is a great place to start. Built on a foundation of innovation, it's the dependable workhorse for industrial painters. From holding, bundling and bright coloured marking to prepping an area for painting, it delivers the industrial-strength performance you can count on. Of course, you wouldn't expect anything less from the company that invented masking tape in the first place.

Product Highlights

- Good conformability to irregular surfaces
- Resists paint bleed-through and offers great paint lines
- Yellow backing ensures good visibility
- Ideal for industrial paint masking, bundling, holding, marking, colour coding and sealing
- Withstands surface temperatures up to 107°C (225°F) for 30 minutes



Strong holding power



Great paint lines



Perfect for labeling



Highly conformable

3M™ Performance Yellow Masking Tape 301+

Tape Size	UPC	SAP SKU	Rolls/Case
301+ Bulk Packaging			
12 mm x 55 m	00051115647499	7000124887	72
18 mm x 55 m	00051115647505	7000124888	48
24 mm x 55 m	00051115647512	7000124889	36
36 mm x 55 m	00051115647529	7000124890	24
48 mm x 55 m	00051115647536	7000124891	24
72 mm x 55 m	00051115647543	7000124892	12
96 mm x 55 m	00051115647550	7000124893	8
1490 mm x 55 m	00051115691089	7000124905	1
301+ Individually Wrapped			
24 mm x 55 m	00051115647567	7000148419	36
36 mm x 55 m	00051115647574	7000148420	24
48 mm x 55 m	00051115647581	7000148421	24

PRODUCT USE: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application. **WARRANTY AND LIMITED REMEDY:** Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price. **LIMITATION OF LIABILITY:** Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



**Industrial Adhesives
and Tapes Division
3M Canada Company**

Post Office Box 5757
London, Ontario N6A 4T1
Canada

1 800 364-3577

www.3M.com/maskingmadesimple
www.3M.com/industrialtapes

3M and Scotch are trademarks of 3M. Used under license in Canada. © 2014, 3M. All rights reserved. 1412-02494E



Learn more about 3M™ Industrial Masking Tapes
at 3M.com/maskingmadesimple
or call 1 800 364-3577.