



Ridgeline® Full Brim ANSI • CSA •

Shell constructed from ABS material // Ratchet suspension is easy to adjust, allowing you to modify the fit while wearing the hat // Available in 4-point and 6-point ratchet suspension // 4-point ratchet suspension may be converted to 6-point ratchet suspension with optional strap [HP6PTSUS] // Replaceable ratchet suspensions available // Replaceable sweat band— padded fabric and polyurethane foam // Passes high temperature (HT) and low temperature (LT) // Custom imprinting available

Vented Full Brim

4-Point Ratchet Vented | 7 Variations

- HP54110V White
- HP54113V ■ Slate Gray
- HP54130V ● Yellow
 - HP54131V ● Hi-Vis Lime
- HP54141V ● Hi-Vis Orange
- HP54160V ■ Blue
 - HP54117V ■ Matte Black Graphite

Hydro Dipped

4-Point Ratchet Hydro Dipped | 10 Variations

- HP54116 ● Matte White Graphite Pattern
- HP54116S • Shiny White Graphite Pattern
- HP54117 ■ Matte Black Graphite Pattern
- HP54117S ● Shiny Black Graphite Pattern
- HP54117V • Matte Black Graphite Pattern (Vented)
- HP54118 ● Matte Copper Pattern
- HP54119 ● Matte Camo Pattern
 - HP54121 ■ Matte Red Pattern
- HP54122 ■ Matte Blue Pattern
 - HP54123 ● Matte Silver Pattern
 - HP54MIX • HP54116 (3), HP54117 (3), HP54118 (3), and HP54119 (3)

Standard Full Brim

4-Point Ratchet | 11 Variations

- HP54110 ● White
 - HP54111 ■ Black
- HP54112 ● Gray
- HP54113 • Slate Gray
- HP54120 ● Red
- HP54130 • Yellow
- HP54131 ● Hi-Vis Lime
- HP54135 ● Green
- HP54141 ● Hi-Vis Orange
- HP54160 • Blue
- HP54170 • Hi-Vis Pink

6-Point Ratchet | 5 Variations

- HP56110 White HP56120 ● Red
- HP56130 Yellow
- HP56135 Green
 - HP56160 Blue







Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)

Suspension: high density polyethylene (HDPE) & high impact nylon

Sweat band: polyester fabric & polyurethane (PU) foam

General Specifications

Weight: 378 gm

Shell thickness: 1.7 - 4 mm

Dimensions: 31 cm x 27 cm x 15.2 cm

Suspension adjust sizing: 6.5 - 8

Suspensions: 4-point suspension may be converted to 6-point suspension with optional street

Standards: ANSI/ISEA Z89.1-2014 and Cert. Mod. - CAN/CSA Z94.1-15

Types: Type 1

Classes: Class E, G, and C (Vented: Class C only)

Optional features: hi-vis colors (HV), lower temperature(LT), higher temperature (HT)

Markings

Types: Type 1 offers protection to the top of the head

Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection

HV: meets all requirements for high visibility

LT: provides protection at low temperatures -22°F

HT: provides protection at high temperatures $140^{\circ}F$

Date code: indicates month and year when the shell was molded – does not indicate service life





Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use

Never alter or modify the shell or suspension system

Inspect the hard hat each time before use and replace if there is ANY sign of damage

Replace hard hat after it receives a considerable impact

Accessories such as liners have not been tested to the requirement of this standard

Clean only with mild soap and lukewarm water

Store hard hat in a clean, dry place that is out of direct sunlight

Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat

Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage