



**V2G-Plus®** ANSI • CE • CSA • Ballistic •



Includes a wide adjustable elastic strap with quick release system for secure fit // TPU frame features excellent resistance to cold and heat // Thermo lens system provides excellent resistance to fog caused by temperature differences in your environment // Special indirect ventilation system located at the top and bottom of frame allows airflow and heat release // Multi-functional goggle with 180° vision protects against chemical splash, sun glare, dust, flying particles, and wind // Outer polycarbonate lens protects against the environment while an inner acetate lens prevents fogging // Inner lens is separated by a thin spacer of air and sealed together with foam // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Passes D3: Droplet and Splash Test // Custom imprinting available

**Black Body with Strap | 2 Variations**

- GB 6410SDT ● ● ● Clear Dual Pane **H2X AF**
- GB 6420SDT ● ● ● Gray Dual Pane **H2X AF**



**V2G-Plus Rx Insert**

RX6400

Accommodates -3.0 to +3.0 prescription lenses // Securely snaps into place above nosepiece // Includes micro-fiber storage case // Take insert to local optometrist for Rx lens installation

**General Specifications**

Weight: 80 gm  
 PD: 68 mm  
 Bridge: 33.5 mm  
 Lens base: 5.5 curve  
 Lens size diagonal: 139 mm  
 Lens size vertical: 63.5 mm  
 Lens thickness: 2.1 mm  
 Overall length (lens - tip): 87 mm  
 Overall width (hinge - hinge): 136 mm  
 Strap Length: 500 mm

**Materials**

Lens: polycarbonate & acetate  
 Foam: polyurethane foam  
 Frame: thermoplastic polyurethane  
 Nosepiece: thermoplastic polyurethane  
 Strap: polyester  
 Strap Holder: polycarbonate

**Part No.**

GB 6410SDT  
 GB 6420SDT

**Lens Marking**

P Z87 + U6 L1.3 X  
 P Z87 + U6 L2.5 X

**Temple Marking**

P Z87 + D3 / P c SEI Z94.3  
 P Z87 + D3 / P c SEI Z94.3

**Lens Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 X: Tested Anti-fog

**UV Filter Transmittance**

U6: .01% max effective far UV • .1% max near UV

**Visible Light Filters**

L1.3: 85% max visible light  
 L2.5: 29% max visible light

**Temple Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 D3: Droplet & Splash Test  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices